

Technical Data Sheet Expanded Perlite







Undated	July	2023	

CHEMICAL ANALYSIS				
Silica	74%			
Aluminium Oxide	14%			
Ferric Oxide	1%			
Calcium Oxide	1.3%			
Magnesium Oxide	0.3%			
Sodium Oxide	3%			
Potassium Oxide	4%			
Titanium Oxide	0.1%			
Heavy Metals	Trace			
Sulphate	Trace			
Moisture Content	0.3%			
Organic Content	< 0.1%			
Thermal Conductivity	0.0361 % @ 0 ºC			

PHYSIC	CAL PROPERTIES
Specific Gravity (g/ml)	0.055-0.30
Colour	Off White
Fusion Point (Deg.C)	1260-1340
Softening Point (Deg.C)	871-1093

The figures quoted in this data sheet are, to the best of our knowledge, representative of the product. Natural products do vary, so these figures are approximations for guidance only. As conditions of use are beyond our control, no liability is accepted for any loss or damage sustained arising from the use of this information or any products. Because of ongoing developments, the product parameters may be changed without notice.

GRADE	P100	PLASTERFINE	P200	P300	P400	P500
Product	Superfine	Fine	Fine	Medium	Medium	Coarse
Loose Bulk Density (kg/m3)	65-95	150-200	45-75	80-120	80-120	80-120
% Retained						
4.75mm		-		0-15%	5-15%	1-15%
3.35mm			-			25-75%
2.80mm				10-25%		
2.36mm				0 0	25-75%	
2.00mm		0		20-40%		10-20%
1.18mm	0-2%	0	0-40%		5-40%	0-10%
0.60mm	15-25%	0-5%	30-60%	40-60%	0-10%	0-3%
0.30mm	40-50%	20-40%	10-40%		0-3%	
0.15mm	60-75%	70-90%	5-30%	80-100%		
PRIMARY APPLICATIONS	P100	PLASTERFINE	P200	P300	P400	P500
Horticulture		-		Х	Х	Х
Construction	Х	Х	Х	Х	Х	Х
Cryogenic Insulation			Х			
Absorbant		1 - 1	Х		Х	
Refractory	Х	Х	Х	Х	Χ	
Plaster	Х	Х				
Pizza Ovens				Х		

AUSPERL PTY LIMITED

Tel: +61 2 8318 7824 • Fax: +61 2 9791 1350 • Email: info@ausperl.com PO BOX 381 Padstow, NSW 2211 • 64 Gow Street, Padstow, NSW 2211

ACN: 605 415 816 • ABN: 39 605 415 816 • www.ausperl.com